



## TECHNICAL DATA SHEET

### ANTIBACTERIAL THERMAL GLOSS 24 MICRON

#### Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Extrusion coated thermal lamination film with **ANTIBACTERIAL** properties and **GLOSS** finish - Both side Corona treated - Low melt adhesive coating inside - Excellent optical properties and good resistance to elongation and tear

Typical Properties					
Graphic Image Films Antibacterial Thermal Gloss	Property		Unit	Test Method	Value
	Thickness		( µm )	ASTM E 252	24
	Yield		m <sup>2</sup> /kg .	ASTM D 4321	46,0
	Unit Weight		g/m <sup>2</sup>		21,7
	Gloss	B	%	ASTM D 2457 60°	95
	Haze	B	%	ASTM 1003	
	Wetting Tension	B	Dynes/cm	ASTM D 2578	39
		A			45
	C.O.F Film/Film (Static)	B/B		ASTM D 1894	0,25
	Application Temperature	A	°C		100-110
	A: Adhesive Side B: Gloss Side				

**Disclaimer** - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic **Image** Films Ltd.  
 Unit 5, Ridge Way, Crendon Industrial Park,  
 Long Crendon, Bucks, HP18 9BF.  
**T:** 01844 208308, **F:** 01844 208608  
**Email:** info.gif@graphicimagefilms.co.uk  
[www.graphicimagefilms.co.uk](http://www.graphicimagefilms.co.uk)