



## TECHNICAL DATA SHEET

### DIGI-STICK SOFT TOUCH MATT 35 MICRON

#### Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Thermal lamination film with **SOFT TOUCH** finish - Smooth velvet feel with good antiscratch properties and excellent clarity by contact - No tonality lost after lamination - Specially formulated high bond low melt adhesive for Digital inks (50% higher adhesive strength than standard litho films)

Typical Properties					
Graphic Image Films Digi-stick Soft Touch	Property		Unit	Test Method	Value
	Thickness		( µm )	ASTM E 252	35
	Yield		m <sup>2</sup> /kg	ASTM D 4321	31,2
			ln <sup>2</sup> /Lb		21937
	Unit Weight		g/m <sup>2</sup>	Der - 009	32.05
	Gloss	B	%	ASTM D 2457 60°	4
	Wetting Tension	B	Dynes/cm	ASTM D 2578	>42
	C.O.F Film/Film	B/B		ASTM D 1894	0.50
	Application Temperature	A	°C		105-115
			°F		221-239
	Lamination Strength	A	N25/mm	ASTM D 882	≥8
			Lb/ln		≥1,82
	A: Adhesive Side    B: Soft Touch Side				

**Disclaimer** - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.  
 Unit 5, Ridge Way, Crendon Industrial Park,  
 Long Crendon, Bucks, HP18 9BF.  
 T: 01844 208308, F: 01844 208608  
 Email: [info.gif@graphicimagefilms.co.uk](mailto:info.gif@graphicimagefilms.co.uk)  
[www.graphicimagefilms.co.uk](http://www.graphicimagefilms.co.uk)