



## TECHNICAL DATA SHEET

### THERMAL GLOSS 24 MICRON

#### Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Extrusion coated thermal lamination film with **GLOSS** finish - Both side Corona treated - Low melt adhesive coating inside - Excellent optical properties and good resistance to elongation and tear

Typical Properties					
Graphic Image Films Thermal Gloss	Property		Unit	Test Method	Value
	Thickness		( µm )	ASTM E 252	24
	Yield		m <sup>2</sup> /kg .	ASTM D 4321	47,62
	Unit Weight		g/m <sup>2</sup>		21,0
	Gloss	B	Gardner	ASTM D 2457 45°	58
	Wetting Tension	B	Dynes/cm	ASTM D 2578	38
		A			44
	C.O.F Film/Film (Static)	B/B		ASTM D 1894	0,27
	C.O.F Film/Film (Kinetic)	B/B			0,25
	Application Temperature	A	°C		100-120
	A: Adhesive Side B: Gloss Side				

**Disclaimer** - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.  
 Unit 5, Ridge Way, Crendon Industrial Park,  
 Long Crendon, Bucks, HP18 9BF.  
 T: 01844 208308, F: 01844 208608  
 Email: [info.gif@graphicimagefilms.co.uk](mailto:info.gif@graphicimagefilms.co.uk)  
[www.graphicimagefilms.co.uk](http://www.graphicimagefilms.co.uk)