



TECHNICAL DATA SHEET

THERMAL METALISED SOFT TOUCH 32 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Extrusion coated thermal lamination film with **METALISED SOFT TOUCH** finish - Print receptive (produces Holographic results with standard inks) - Smooth velvet feel with good antiscratch properties - Both side Corona treated - Low melt adhesive coating inside

Typical Properties					
Graphic Image Films Thermal Metalised Soft Touch	Property		Unit	Test Method	Value
	Thickness		(µm)	ASTM E 252 84	32
	Yield		m ² /kg .	ASTM D 4321	34,0
	Unit Weight		g/m ²	Derprosa - 009	29,4
	Optical Density		%	ASTM 1003 00	2,3
	Wetting Tension	B	Dynes/cm	ASTM D 2578 84	>45
	C.O.F Film/Film	B/B		ASTM D 1894 90	0,45
	Application Temperature	A	°C		90-120
	Lamination Strength	A	N25/mm		> 7,5
	A: Adhesive Side B: Metalised Soft Touch Side				

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk