



TECHNICAL DATA SHEET

WET METALISED SOFT TOUCH MATT 20 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Wet lamination film with **METALISED SOFT TOUCH** finish - Print receptive (produces Holographic results with standard inks) - Smooth velvet feel with good antiscratch properties - Both side Corona treated

| Typical Properties | | | | | |
|---|--|-----|----------------------|--------------|-------|
| Graphic Image Films Wet Met Soft Touch | Property | | Unit | Test Method | Value |
| | Thickness | | (µm) | ASTM E 252 | 20 |
| | Yield | | m ² /kg . | ASTM D 4321 | 54,8 |
| | Unit Weight | | g/m ² | Der - 009 | 18,3 |
| | Optical Density | | % | ASTM 1003 00 | 2,3 |
| | Wetting Tension | B | Dynes/cm | ASTM D 2578 | 45 |
| | | A | | | 36 |
| | C.O.F Film/Film | B/B | | ASTM D 1894 | 0,45 |
| | A: Inside B: Metalised Soft Touch Side | | | | |

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk