



TECHNICAL DATA SHEET

DIGI-STICK GLOSS 24 MICRON

Product Description

Bi-axially Oriented Polypropylene Film (BOPP) - Extrusion coated thermal lamination film with **GLOSS** finish - Specially formulated high bond low melt adhesive for Digital Toner inks (50% higher adhesive strength than standard litho films) - Excellent optical properties

Typical Properties					
Graphic Image Films Digi-stick Gloss	Property		Unit	Test Method	Value
	Thickness		(µm)	ASTM E 252	24
	Yield		m ² /kg .	ASTM D 4321	45,7
			ln ² /Lb		32105
	Unit Weight		g/m ²	Der - 009	21,88
	Gloss	B	%	ASTM D 2457 60°	95
		A			15
	Wetting Tension	B	Dynes/cm	ASTM D 2578	39
	C.O.F Film/Film	B/B		ASTM D 1894	0,40
	Application Temperature	A	°C		105-115
			°F		221-239
	Lamination Strength	A	N25/mm	ASTM D 882	7,5
			Lb/In		1,71
	A: Adhesive Side B: Gloss Side				

Disclaimer - The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk