



TECHNICAL DATA SHEET

WET SOFT TOUCH MATT 17 MICRON

Product Description

Specially designed to laminate high-quality media, this matt lamination film has an agreeable, velvety aspect similar to peach skin and affords excellent clarity to the underlying colours.

Typical Properties

Properties	Unit	Test Method	Typical Value
General			
Nominal Thickness	(μm) Gauge	ASTM E 252	17 68
Yield	m^2/kg	ASTM D 4321	64.6
Density	g/m^2		15.5
Mechanical			
Tensile Strength	Mpa	MD ASTM D882 TD ASTM D882	115 235
Elongation At Break	%	MD ASTM D882 TD ASTM D882	165 50
Coefficient of friction	film to film	ASTM D1894	0.45
Surface Tension	dyne/cm	ASTM D 2578	42
Optical			
Haze	%		95.0
Gloss Value	%		4.0
Thermal			
Heat Shrinkage	120°C, 5min	MD % ASTM D1204 TD % ASTM D1204	4.0 1.5
Water Vapour transmission rate			
Oxygen transmission rate			

This Information is the best currently available on the subject. The results should, however, only be regarded as a general guide to material properties and not as a guarantee. Some of the properties can be changed as a result of supplier's efforts to improve the quality or production efficiency of the subject.

Graphic Image Films Ltd.
 Unit 5, Ridge Way, Crendon Industrial Park,
 Long Crendon, Bucks, HP18 9BF.
 T: 01844 208308, F: 01844 208608
 Email: info.gif@graphicimagefilms.co.uk
www.graphicimagefilms.co.uk